



Spiralbohrer · kanüliert · AO
Twist drills · cannulated · AO



| S 28... | Ø (mm) | Ø (mm) Kanülierung / Cannulation | S / FL # | KL / HL (mm) | GL / TL (mm) | effektive Länge / effective length (mm) | Anschluss / Connection |
|----------------|-----------|-------------------------------------|-------------|-----------------|-----------------|--|------------------------|
| SC2805.098 STE | 2,0 | 1,2 | 3 | 35 | 150 | 50 | AO |
| SC2805.098 | 2,0 | 1,2 | 3 | 35 | 150 | 50 | AO |
| SC2803.098 STE | 2,7 | 1,4 | 4 | 50 | 160 | 130 | AO |
| SC2803.098 | 2,7 | 1,4 | 4 | 50 | 160 | 130 | AO |
| SC2801.098 STE | 3,2 | 1,7 | 4 | 50 | 170 | 140 | AO |
| SC2801.098 | 3,2 | 1,7 | 4 | 50 | 170 | 140 | AO |
| SC2804.098 STE | 3,5 | 1,4 | 4 | 50 | 160 | 130 | AO |
| SC2804.098 | 3,5 | 1,4 | 4 | 50 | 160 | 130 | AO |
| SC2802.098 STE | 4,5 | 1,7 | 4 | 50 | 170 | 140 | AO |
| SC2802.098 | 4,5 | 1,7 | 4 | 50 | 170 | 140 | AO |

