




Spiralbohrer · AO
Twist drills · AO



S27...	Ø (mm)	S/FL #	KL/HL (mm)	Gesamtlänge/total length (mm)	effektive Länge/effective length (mm)	Anschluss/Connection
S2709.098 STE	1,1	2	16	60	30	AO
S2709.098	1,1	2	16	60	30	AO
S2710.098 STE	1,5	2	30	85	55	AO
S2710.098	1,5	2	30	85	55	AO
S2711.098 STE	1,5	2	30	110	80	AO
S2711.098	1,5	2	30	110	80	AO
S2712.098 STE	1,5	2	30	125	95	AO
S2712.098	1,5	2	30	125	95	AO
S2713.098 STE	1,8	2	30	100	70	AO
S2713.098	1,8	2	30	100	70	AO
S2714.098 STE	2,0	2	50	100	70	AO
S2714.098	2,0	2	50	100	70	AO
S2715.098 STE	2,0	2	50	125	95	AO
S2715.098	2,0	2	50	125	95	AO
S2716.098 STE	2,4	2	50	100	70	AO
S2716.098	2,4	2	50	100	70	AO
S2717.098 STE (gold/golden)	2,5	2	50	180	150	AO
S2717.098 (gold/golden)	2,5	2	50	180	150	AO
S2718.098 STE (gold/golden)	2,5	2	50	110	80	AO
S2718.098 (gold/golden)	2,5	2	50	110	80	AO
S2719.098 STE	2,7	2	50	100	70	AO
S2719.098	2,7	2	50	100	70	AO
S2720.098 STE	2,7	2	50	125	95	AO
S2720.098	2,7	2	50	125	95	AO
S2721.098 STE	3,2	2	50	195	165	AO
S2721.098	3,2	2	50	195	165	AO
S2722.098 STE	3,2	2	50	145	115	AO
S2722.098	3,2	2	50	145	115	AO
S2723.098 STE	3,2	2	50	225	195	AO
S2723.098	3,2	2	50	225	195	AO
S2724.098 STE	3,5	2	50	110	80	AO
S2724.098	3,5	2	50	110	80	AO
S2725.098 STE	3,5	2	50	195	165	AO
S2725.098	3,5	2	50	195	165	AO
S2726.098 STE	4,0	2	50	225	195	AO
S2726.098	4,0	2	50	225	195	AO
S2727.098 STE	4,5	2	50	145	115	AO
S2727.098	4,5	2	50	145	115	AO
S2728.098 STE	4,5	2	50	195	165	AO
S2728.098	4,5	2	50	195	165	AO
S2729.098 STE	6,0	2	50	195	165	AO
S2729.098	6,0	2	50	195	165	AO

